



Trading Document - Flat Rolled Products

The document presents all the most important requirements regarding the product supply of Alumeco. The information presented below will no longer be stated on our purchase orders. This means that Alumeco's supplier is obliged to save this document and comply with the requirements contained therein.

By confirming your order to Alumeco, you agree to fulfill the above mentioned conditions.

Quality datasheets of aluminum sheets and plates per alloy (ver. 1.0.)

Stockal-liquid polyester prepainted coils EN AW-3105 (RAL 9005).....	4
Stockal-liquid polyester prepainted coils, EN AW-3105 (RAL 7016).....	5
Stockal-liquid polyester prepainted coils, EN AW-5010 H42 (RAL 9010)	6
Stockal-liquid polyester prepainted coils, EN AW-5050 (RAL 9005, 9010).....	7
Aluminium polyester lacquer coils, EN AW-3003 (RAL 9010) G85.....	8
Aluminium polyester lacquer coils, EN AW-3105 (RAL 9010) G85.....	9
Aluminium coil in alloy EN AW-1050A H14 STUCCO embossed, 250 kg, 500 kg /1000 kg	10
Aluminium coil in alloy EN AW-3003 H14, 250 kg / 1000 kg.....	11
Aluminium coil in alloy EN AW-5052 H22, 500 kg / 1000 kg.....	12
Aluminium Mother Coils in alloy EN AW-1050A H14	13
Aluminium Mother Coils in alloy EN AW-5005A H24 NQ	14
Aluminium Mother Coils in alloy EN AW-5005A H14 Norf	15
Aluminium Mother Coils in alloy EN AW-5754 H22/ H111	16
Aluminium sheets in alloy EN AW-1050A H14	17
Aluminium sheets in alloy EN AW-1050A H111	17
Aluminium sheets in alloy EN AW-1050 H14 F1 / F1L	18
Aluminium sheets in alloy EN AW-5754 H22/ H111	18
Aluminium sheets in alloy EN AW-5754 H111 F1 / F1L	19
Aluminium sheets in alloy EN AW-5083 H111	19
Aluminium sheets in alloy EN AW-5083 H111, DNV, LRS	20
Aluminium sheets in alloy EN AW-5083 H321, DNV, LRS	20
Aluminium sheets anodizing quality in alloy EN AW-5005 H14 (55HX).....	21
Aluminium sheets anodizing in alloy EN AW-5005 H14, 10µm / 15µm (55HX)	21
Aluminium sheets anodizing in alloy EN AW-5005 H14, 10µm (Stainless Steel look- B57S)	22
Aluminium painted sheets in alloy EN AW-3003 (RAL 9005) G26-50.....	23
Aluminium painted sheets in alloy EN AW-3003 (RAL 9005) G35.....	23
Aluminium painted sheets in alloy EN AW-3003 (RAL 9006) G35.....	24
Aluminium painted sheets in alloy EN AW-3003 (RAL 9010) G35.....	24
Aluminium painted sheets in alloy EN AW-3005 (RAL 7016) G35.....	25
Aluminium painted sheets in alloy EN AW-3005 (RAL 7016) G90.....	25
Aluminium painted sheets in alloy EN AW-3005 (RAL 9005) G35.....	26
Aluminium painted sheets in alloy EN AW-3005 (RAL 9006) G35.....	26
Aluminium painted sheets in alloy EN AW-3005 (RAL 9010) G35.....	27
Aluminium plates in alloy - EN AW-1050A, H111	28
Aluminium plates in alloy - EN AW-2017A, T451	29
Aluminium plates in alloy - EN AW-5754 H111	30

Aluminium plates in alloy - EN AW-5083 H111	31
Aluminium plates in alloy - EN AW-6061 T651	32
Aluminium plates in alloy - EN AW-6082 T651	33
Aluminium plates in alloy - EN AW-7075 T6/ T651	34
Aluminium treadplates in alloy EN AW-5754 H114.....	35
Homogenized aluminum blocks in alloy EN AW-1370 cast temp	36
Homogenized aluminum blocks in alloy EN AW-5083 cast temp.	37
Homogenized aluminum blocks in alloy EN AW-7021 cast temp	38
Aluminium cast milled plate in alloy - EN AW-5083 O3	39
Aluminium cast milled plate in alloy - EN AW-5754 V-cast O3	40

Stockal-liquid polyester prepainted coils EN AW-3105 (RAL 9005)

EN AW 3105 – coils Alumeco ApS	Alloy name: 3105 International alloy name: EN AW 3105 Chemical Symbol: EN AW - AlMn0.5Mg0.5
Temper: H44 ID: 508 mm Front side: AC8301/26 (liquid polyester equiv. RAL9005) with foil Reverse side: AC6325/26 (clear protective primer) Quantity tolerance: +/- 10% Packing: Eye to side	Important norms and literature EN 573-3 EN 515 EN 573-3, EN 1396, EN 485-1/2/3/4, EN 515, EN 10204

Stockal-liquid polyester prepainted coils, EN AW-3105 (RAL 7016)

EN AW 3105 – coils Alumeco ApS	Alloy name: 3105 International alloy name: EN AW 3105 Chemical Symbol: EN AW - AlMn0.5Mg0.5
Temper: H44 ID: 508 mm Front: Colour 1. side AC18H2 Shining white Colour 2. side AC68F6 Back coating blue Foil Neutral easy peeling UVA Reverse side: AC6325/26 (clear protective primer) Quantity tolerance: +/- 10% Packing: Eye to side	Important norms and literature EN 573-3 EN 515 EN 573-3, EN 1396, EN 485-1/2/3/4, EN 515, EN 10204

Stockal-liquid polyester prepainted coils, EN AW-5010 H42 (RAL 9010)

EN AW 5010 – coils Alumeco ApS	Alloy name: 5010 International alloy name: EN AW 5010 Chemical Symbol: EN AW - AlMg1.5(C)
Temper: H42 ID: 508 mm Front side: RAL9010: 18E3/26A, White gloss 80 with protective film Reverse side: AC6325/26 (clear protective primer) Quantity tolerance: +/- 10% Packing: Eye to side	Important norms and literature EN 573-3 EN 515 EN 573-3, EN 1396, EN 485-1/2/3/4, EN 515, EN 10204

Stockal-liquid polyester prepainted coils, EN AW-5050 (RAL 9005, 9010)

EN AW 5050 – coils Alumeco ApS	Alloy name: 5050 International alloy name: EN AW 5050 Chemical Symbol: EN AW - AlMg1.5(C)
ID: 508 mm Front side: RAL9005: AC8301/26 (liquid polyester equiv.) RAL9010: 18E3/26A, White gloss 80 with foil Reverse side: AC6325/26 (clear protective primer) Quantity tolerance: +/- 10% Packing: Eye to side	Important norms and literature EN 573-3 EN 515 EN 573-3, EN 1396, EN 485-1/2/3/4, EN 515, EN 10204

Aluminium polyester lacquer coils, EN AW-3003 (RAL 9010) G85

EN AW 3003 – coils Alumeco ApS	Alloy name: 3003 International alloy name: EN AW 3003 Chemical Symbol: EN AW - AlMn1
Temper: H45 ID: 600 mm OD: max. 1800 mm Front side: White RAL 9010 / NCS0502Y gloss 85 Reverse side: Backside standard grey/clear protection coating Quantity tolerance: +/- 10% Packing: Eye to side	Important norms and literature EN 573-3 EN 515 EN 573-3, EN 1396, EN 485-1, EN 515, EN 10204

Aluminium polyester lacquer coils, EN AW-3105 (RAL 9010) G85

EN AW 3105 – coils Alumeco ApS	Alloy name: 3105 International alloy name: EN AW 3105 Chemical Symbol: EN AW - AlMn0.5Mg0.5
Temper: H45 ID: 600 mm OD: max. 1800 mm Front side: White RAL 9010 / NCS0502Y gloss 85 Reverse side: Backside standard grey/clear protection coating Tension: levelled and with trimmed edges. Quantity tolerance: +/- 10% Packing: Eye to side	Important norms and literature EN 573-3 EN 515 EN 573-3, EN 1396, EN 485-1, EN 515, EN 10204

Aluminium coil in alloy EN AW-1050A H14 STUCCO embossed, 250 kg, 500 kg /1000 kg

EN AW 1050A – coils Alumeco ApS	Alloy name: 1050A International alloy name: EN AW 1050A Chemical Symbol: EN AW – Al99.5
Temper: H14 ID: 500 mm Tension levelled and slightly oiled, not degreased. Packing: 250 kg – eye to sky 500-1000 kg - Eye to side with cardboard core Plastic wrapping: Coils to be wrapped separately with plastic around and on top cardboard. The coils must NOT be wrapped together. Quantity tolerance: +/- 10%	Important norms and literature EN 573-3 EN 515 EN 573-3, 485-1/2/3/4, 15088, EN 515, EN 10204

Aluminium coil in alloy EN AW-3003 H14, 250 kg / 1000 kg

EN AW 3003 – coils Alumeco ApS	Alloy name: 3003 International alloy name: EN AW 3003 Chemical Symbol: EN AW – AlMn1Cu
Temper: H14 ID: 500 mm Tension levelled and slightly oiled, not degreased. Packing: 250 kg - eye to sky 1000 kg – eye to side Plastic wrapping: Coils to be wrapped separately with plastic around and on top cardboard. The coils must NOT be wrapped together. Quantity tolerance: +/- 10%	Important norms and literature EN 573-3 EN 515 EN 573-3, 485-1/2/3/4, 15088, EN 515, EN 10204

Aluminium coil in alloy EN AW-5052 H22, 500 kg / 1000 kg

EN AW 5052 – coils Alumeco ApS	Alloy name: 5052 International alloy name: EN AW 5052 Chemical Symbol: EN AW – Al-Mg2.5
Temper: H22 ID: 500 mm Tension levelled and slightly oiled, not degreased. Packing: 500 kg – eye to side 1000 kg – eye to side Plastic wrapping: Coils to be wrapped separately with plastic around and on top cardboard. The coils must NOT be wrapped together. Quantity tolerance: +/- 10%	Important norms and literature EN 573-3 EN 515 EN 573-3, 485-1/2/3/4, 15088, EN 515, EN 10204

Aluminium Mother Coils in alloy EN AW-1050A H14

EN AW 1050A – Aluminium coils Alumeco ApS	Alloy name: 1050A International alloy name: EN AW 1050A Chemical Symbol: EN AW – Al99,5
Temper: H14 Quantity tolerance: +/- 10% Special requirements: Tension levelled and slightly oiled Thickness tolerance: +0/ -1/2 EN485-4 tolerance Inside Diameter: We can only use coils with inner diameter 460-520mm or 590-620 mm in our production. Outside diameter: Maximum 1800 mm Coil net weight maximum limit: 10.000 kg.	Important norms and literature EN 573-3 EN 515 EN: 573-3, 485-1/2/4, 10204 EN 515

Aluminium Mother Coils in alloy EN AW-5005A H24 NQ
--

EN AW 5005A – Aluminium coils Alumeco ApS	Alloy name: 5005A International alloy name: EN AW 5005A Chemical Symbol: EN AW – AlMg1(C)
Temper: H24 NQ Quantity tolerance: +/- 10% Thickness tolerance: +0/ -1/2 EN485-4 tolerance Inside Diameter We can only use coils with inner diameter 460-520mm or 590-620 mm in our production. Outside diameter: Maximum 1800 mm Coil net weight maximum limit: Coil net weight maximum limit: 10.000 kg.	Important norms and literature EN 573-3 EN 515 EN: 573-3, 485-1/2/4, 10204 EN 515

Aluminium Mother Coils in alloy EN AW-5005A H14 Norf
--

EN AW 5005A – Aluminium coils Alumeco ApS	Alloy name: 5005A International alloy name: EN AW 5005A Chemical Symbol: EN AW – AlMg1(C)
Temper: H14 Norf Quantity tolerance: +/- 10% Thickness tolerance: +0/ -1/2 EN485-4 tolerance Inside Diameter We can only use coils with inner diameter 460-520mm or 590-620 mm in our production. Outside diameter: Maximum 1800 mm Coil net weight maximum limit: Coil net weight maximum limit: 10.000 kg.	Important norms and literature EN 573-3 EN 515 EN: 573-3, 485-1/2/4, 10204 EN 515

Aluminium Mother Coils in alloy EN AW-5754 H22/ H111

EN AW 5754 – Aluminium coils Alumeco ApS	Alloy name: 5754 International alloy name: EN AW 5754 Chemical Symbol: EN AW – AlMg3
Temper: H22 Quantity tolerance: +/- 10% Special requirements: Tension levelled and slightly oiled Thickness tolerance: +0/ -1/2 EN485-4 tolerance Inside Diameter We can only use coils with inner diameter 460-520mm or 590-620 mm in our production. Outside diameter: Maximum 1800 mm Coil net weight maximum limit: Coil net weight maximum limit: 10.000 kg.	Important norms and literature EN 573-3 EN 515 EN: 573-3, 485-1/2/4, 10204 EN 515

Aluminium sheets in alloy EN AW-1050A H14

EN AW 1050A – Sheets Alumeco ApS	Alloy name: 1050A International alloy name: EN AW 1050 Chemical Symbol: EN AW – Al99,5
Temper: H14 Quantity tolerance: +/- 10% Sheets must not be stamped	Important norms and literature EN 573-3 EN 515 EN: 573-3, 485-1/2/4, 10204 EN 515

Aluminium sheets in alloy EN AW-1050A H111

EN AW 1050 – Sheets Alumeco ApS	Alloy name: 1050 International alloy name: EN AW 1050 Chemical Symbol: EN AW – Al99,5
Temper: H111 Quantity tolerance: +/- 10% Sheets must not be stamped Special requirements: Deep drawn quality. Slightly oiled, plane, and stretched	Important norms and literature EN 573-3 EN 515 EN: 573-3, 485-1/2/4, 10204

Aluminium sheets in alloy EN AW-1050 H14 F1 / F1L

EN AW 1050 – Sheets Alumeco ApS	Alloy name: 1050 International alloy name: EN AW 1050 Chemical Symbol: EN AW – Al99,5
Temper: H14 Quantity tolerance: +/- 10% Sheets must not be stamped. Foil requirement: F1 With protective foil 80my on 1 side. F1L With protective laser foil on 1 side.	Important norms and literature EN 573-3 EN 515 EN: 573-3, 485-1/2/3, 10204

Aluminium sheets in alloy EN AW-5754 H22/ H111

EN AW 5754 – Sheets Alumeco ApS	Alloy name: 5754 International alloy name: EN AW 5754 Chemical Symbol: EN AW – AlMg3
Temper: H22 Quantity tolerance: +/- 10% Sheets must not be stamped	Important norms and literature EN 573-3 EN 515 EN: 573-3, 485-1/2/4, 10204

Aluminium sheets in alloy EN AW-5754 H111 F1 / F1L

EN AW 5754 – Sheets Alumeco ApS	Alloy name: 5754 International alloy name: EN AW 5754 Chemical Symbol: EN AW – AlMg3
Temper: H111 Quantity tolerance: +/- 10% Sheets must not be stamped Foil requirement: F1 With protective foil 80my on 1 side. F1L With protective laser foil on 1 side.	Important norms and literature EN 573-3 EN 515 EN: 573-3, 485-1/2/4, 10204

Aluminium sheets in alloy EN AW-5083 H111

EN AW 5083 – Sheets Alumeco ApS	Alloy name: 5083 International alloy name: EN AW 5083 Chemical Symbol: EN AW – AlMg4,5Mn0.7
Temper: H111 Quantity tolerance: +/- 10%	Important norms and literature EN 573-3 EN 515 EN: 573-3, 485-1/2/4, 10204

Aluminium sheets in alloy EN AW-5083 H111, DNV, LRS

EN AW-5083 H111 – Aluminium sheets Alumeco ApS	Alloy name: 5083 International alloy name: EN AW-5083 Chemical Symbol: AlMg4.5Mn0.7
Temper: H111 Quantity tolerance: +/-10% Marking: Each plate must be marked with producer, alloy, temper, charge-no and approval Packing: With paper interleaved Certificate: As marked in material description Certificate 3.2/DNV Rules for ships. Pt2, ch2/LRS	Important norms and literature EN 573-3 EN 515 573-3, 485-1/2/3, 515, CE 10204

Aluminium sheets in alloy EN AW-5083 H321, DNV, LRS

EN AW-5083 H321 – Aluminium sheets Alumeco ApS	Alloy name: 5083 International alloy name: EN AW-5083 Chemical Symbol: AlMg4.5Mn0.7
Temper: H321 Quantity tolerance: +/-10% Marking: Each plate must be marked with producer, alloy, temper, charge-no and approval Packing: With paper interleaved Certificate: As marked in material description Certificate 3.2/DNV Rules for ships. Pt2, ch2/LRS	Important norms and literature EN 573-3 EN 515 Corrosion testing in accordance to: ASTM B 928-7 G66 - G67

Aluminium sheets anodizing quality in alloy EN AW-5005 H14 (55HX)

EN AW 5005 – Aluminium pre-anodized sheets Alumeco ApS	Alloy name: 5005 International alloy name: EN AW-5005 Chemical Symbol: AlMg0.5
Temper: H14 Foil: on one side / none Quantity tolerance: +/- 10%	Important norms and literature EN 573-3 EN 515 EN 573-3, 515, 485-1/2/3/4, CE 10204

Aluminium sheets anodizing in alloy EN AW-5005 H14, 10µm / 15µm (55HX)

EN AW 5005 – Aluminium anodized sheets Alumeco ApS	Alloy name: 5005 International alloy name: EN AW-5005 Chemical Symbol: AlMg0.5
Anodized quality/ micron: 10µm / 15µm Temper: H14 Foil: on one side Quantity tolerance: +/- 10%	Important norms and literature EN 573-3 EN 515 EN 573-3, 515, 485-1/2/3/4, 7599, CE 10204

Aluminium sheets anodizing in alloy EN AW-5005 H14, 10µm (Stainless Steel look- B57S)

EN AW 5005 – Aluminium anodized sheets (B57S) Alumeco ApS	Alloy name: 5005 International alloy name: EN AW-5005 Chemical Symbol: AlMg0.5
Anodized quality/ micron: 10 µm B10 light bronze anodized Stainless steel look Temper: H14 Foil: on one side Quantity tolerance: +/- 10%	Important norms and literature EN 573-3 EN 515 EN 573-3, 515, 485-1/2/3/4, 7599, CE 10204

Aluminium painted sheets in alloy EN AW-3003 (RAL 9005) G26-50

EN AW 3003 – Sheets Alumeco ApS	Alloy name: 3003 International alloy name: EN AW 3003 Chemical Symbol: EN AW – AlMn1
Temper: H44 Topside: Polyester paint RAL 9010 gloss 26-50% P03G 9005 H With foil 80 my PVC-foil 1 side Backside: Protective lacquer 5µm +/- 2µm Quantity tolerance: +/- 10%	Important norms and literature EN 573-3 EN 515 EN: 573-3, 485-1/4, 1396, 10204

Aluminium painted sheets in alloy EN AW-3003 (RAL 9005) G35

EN AW 3003 – Sheets Alumeco ApS	Alloy name: 3003 International alloy name: EN AW 3003 Chemical Symbol: EN AW – AlMn1
Temper: H44 Topside: Polyester paint RAL 9005 gloss 35 With foil 80 my PVC-foil Backside: Standard grey/clear protection coating Quantity tolerance: +/- 10% Packing: With paper interleaves	Important norms and literature EN 573-3 EN 515 EN: 573-3, 485-1/4, 1396, 10204

Aluminium painted sheets in alloy EN AW-3003 (RAL 9006) G35

EN AW 3003 – Sheets Alumeco ApS	Alloy name: 3003 International alloy name: EN AW 3003 Chemical Symbol: EN AW – AlMn1
Temper: H44 Topside: Polyester paint RAL 9006 gloss 35 With foil 80 my PVC-foil Backside: Standard grey/clear protection coating Quantity tolerance: +/- 10% Packing: With paper interleaves	Important norms and literature EN 573-3 EN 515 EN: 573-3, 485-1/4, 1396, 10204

Aluminium painted sheets in alloy EN AW-3003 (RAL 9010) G35

EN AW 3003 – Sheets Alumeco ApS	Alloy name: 3003 International alloy name: EN AW 3003 Chemical Symbol: EN AW – AlMn1
Temper: H44 Topside: Polyester paint RAL 9010 gloss 35 With foil 80 my PVC-foil Backside: Standard grey/clear protection coating Quantity tolerance: +/- 10% Packing: With paper interleaves	Important norms and literature EN 573-3 EN 515 EN: 573-3, 485-1/4, 1396, 10204

Aluminium painted sheets in alloy EN AW-3005 (RAL 7016) G35

EN AW 3005 – Sheets Alumeco ApS	Alloy name: 3005 International alloy name: EN AW 3005 Chemical Symbol: EN AW – AlMn1Mg0.5
Temper: H44 Topside: Polyester paint RAL 7016 gloss 35 With foil 80 my PVC-foil Backside: Standard grey/clear protection coating Quantity tolerance: +/- 10% Packing: With paper interleaves	Important norms and literature EN 573-3 EN 515 EN: 573-3, 485-1/4, 1396, 10204

Aluminium painted sheets in alloy EN AW-3005 (RAL 7016) G90

EN AW 3005 – Sheets Alumeco ApS	Alloy name: 3005 International alloy name: EN AW 3005 Chemical Symbol: EN AW – AlMn1Mg0.5
Temper: H44 Topside: Polyester paint RAL 7016 gloss 90 With foil 80 my PVC-foil Backside: Standard grey/clear protection coating Quantity tolerance: +/- 10% Packing: With paper interleaves	Important norms and literature EN 573-3 EN 515 EN: 573-3, 485-1/4, 1396, 10204

Aluminium painted sheets in alloy EN AW-3005 (RAL 9005) G35

EN AW 3005 – Sheets Alumeco ApS	Alloy name: 3005 International alloy name: EN AW 3005 Chemical Symbol: EN AW – AlMn1Mg0.5
Temper: H44 Topside: Polyester paint RAL 9005 gloss 35 With foil 80 my PVC-foil Backside: Standard grey/clear protection coating Quantity tolerance: +/- 10% Packing: With paper interleaves	Important norms and literature EN 573-3 EN 515 EN: 573-3, 485-1/4, 1396, 10204

Aluminium painted sheets in alloy EN AW-3005 (RAL 9006) G35

EN AW 3005 – Sheets Alumeco ApS	Alloy name: 3005 International alloy name: EN AW 3005 Chemical Symbol: EN AW – AlMn1Mg0.5
Temper: H44 Topside: Polyester paint RAL 9006 gloss 35 With foil 80 my PVC-foil Backside: Standard grey/clear protection coating Quantity tolerance: +/- 10% Packing: With paper interleaves	Important norms and literature EN 573-3 EN 515 EN: 573-3, 485-1/4, 1396, 10204

Aluminium painted sheets in alloy EN AW-3005 (RAL 9010) G35

EN AW 3005 – Sheets Alumeco ApS	Alloy name: 3005 International alloy name: EN AW 3005 Chemical Symbol: EN AW – AlMn1Mg0.5
Temper: H44 Topside: Polyester paint RAL 9010 gloss 35 With foil 80 my PVC-foil Backside: Standard grey/clear protection coating Quantity tolerance: +/- 10% Packing: With paper interleaves	Important norms and literature EN 573-3 EN 515 EN: 573-3, 485-1/4, 1396, 10204

Aluminium plates in alloy - EN AW-1050A, H111

EN AW-1050 - Aluminium plates Alumeco ApS	Alloy name: 1050A International alloy name: EN AW-1050A Chemical Symbol: Al 99.5
Temper: H111 Quantity Tolerance: +/- 10 % Marks Plate: Each plate must be marked with alloy, temper and charge-no. Packing: In packages of 1500kg With paper interleaves Surface: Not brushed	Important norms and literature EN 573-3 EN 515 EN: 573-3, 485-1/2/3/4, 515, EN 10204

Aluminium plates in alloy - EN AW-2017A, T451

EN AW-2017A - Aluminium plates Alumeco ApS	Alloy name: 2017A International alloy name: EN AW-2017A Chemical Symbol: AlCu4MgSiA
Temper: T451 stretched Thickness tolerance: -0/+1/2EN Quantity Tolerance: +/- 10 % Edges: With sawn edges Marks Plate: Each plate must be marked with alloy, temper and charge-no. Packing: With paper interleaves Surface: Not brushed For thickness up to 20 mm including surface is brushed by default	Important norms and literature EN 573-3 EN 515 EN: 573-3, 485-1/2/3, 515, EN 10204

Aluminium plates in alloy - EN AW-5754 H111

EN AW-5754 - Aluminium plates Alumeco ApS	Alloy name: 5754 International alloy name: EN AW-5754 Chemical Symbol: AlMg3
Temper: H111 stretched Thickness Tolerance: full slabs: -0/+1/2EN not full slabs: standard tolerance acc. to EN Quantity Tolerance: +/- 10 % Edges: With sawn edges Marks Plate: Each plate must be marked with alloy, temper and charge-no. Packing: With paper interleaves Surface: Not brushed	Important norms and literature EN 573-3 EN 515 EN: 573-3, 485-1/2/3, 515, EN 10204

Aluminium plates in alloy - EN AW-5083 H111

EN AW-5083 - Aluminium plates Alumeco ApS	Alloy name: 5083 International alloy name: EN AW-5083 Chemical Symbol: AlMg4.5Mn0.7
Temper: H111 stretched Thickness Tolerance: -0/+1/2EN Quantity Tolerance: +/- 10 % Edges: With sawn edges Marks Plate: Each plate must be marked with alloy, temper and charge-no. Packing: With paper interleaves Surface: Not brushed	Important norms and literature EN 573-3 EN 515 EN 573-3, 485-1/2/3, 515, EN 10204

Aluminium plates in alloy - EN AW-6061 T651

EN AW-6061 - Aluminium plates Alumeco ApS	Alloy name: 6061 International alloy name: EN AW-6061 Chemical Symbol: AlMg1SiCu
Temper: T651 stretched Thickness tolerance: -0/+1/2EN Quantity Tolerance: +/- 10 % Edges: With sawn edges Marks Plate: Each plate must be marked with alloy, temper and charge-no. Packing: With paper interleaves Surface: Not brushed For thickness up to 20 mm including surface is brushed by default	Important norms and literature EN 573-3 EN 515 EN 573-3, 485-1/2/3, 515, EN 10204

Aluminium plates in alloy - EN AW-6082 T651

EN AW-6082 T651- Aluminium plates Alumeco ApS	Alloy name: 6082 International alloy name: EN AW-6082 T651 Chemical Symbol: AlZn5,5MgCu
Temper: T651 stretched Thickness tolerance.: -0/+1/2EN Quantity Tolerance: +/- 10 % Edges: With sawn edges Marks Plate: Each plate must be marked with alloy, temper and charge-no. Packing: With paper interleaves Surface Acc. To thickness: 1-6mm not brushed >6mm brushed	Important norms and literature EN 573-3 EN 515 EN: 573-3, 485-1/2/3, 515, EN 10204

Aluminium plates in alloy - EN AW-7075 T6/ T651

EN AW-7075 - Aluminium plates Alumeco ApS	Alloy name: 7075 International alloy name: EN AW-7075 Chemical Symbol: AlZn5,5MgCu
Temper: T6/T651 stretched Thickness Tolerance: -0/+1/2EN Quantity Tolerance: +/- 10 % Edges: With sawn edges Marks Plate: Each plate must be marked with alloy, temper and charge-no. Packing: With paper interleaves Surface: Not brushed For thickness up to 20 mm including surface is brushed by default	Important norms and literature EN 573-3 EN 515 EN 573-3, 485-1/2/3, 515, EN 10204

Aluminium treadplates in alloy EN AW-5754 H114
--

EN AW 5754 – Treadplates Alumeco ApS	Alloy name: 5754 International alloy name: EN AW 5754 Chemical Symbol: EN AW – AlMg3
Temper: H114 Quintet pattern, five-bar Quantity tolerance: +/- 10%	Important norms and literature EN 573-3 EN 515 EN573-3, EN515, EN 485-1/2/3/4 and EN 1386

Homogenized aluminum blocks in alloy EN AW-1370 cast temp

EN AW 1370 – Aluminium blocks Alumeco ApS	Alloy name: 1370 International alloy name: EN AW 1370 Chemical Symbol: Al99.7
Temper: cast tempered Quantity tolerance: +/- 10% Shape of block: Blocks must be Sawn in both ends. Flat edged. Block's max weight: 11.000 kg Transportation & Loading of Truck: Loading from the side Loading only using forklift Packing lists: must contain charge number	Important norms and literature EN 573-3 EN 515 EN 487, EN 515, EN 573-3

Homogenized aluminum blocks in alloy EN AW-5083 cast temp.

EN AW 5083 – Aluminium blocks Alumeco ApS	Alloy name: 5083 International alloy name: EN AC 5083 Chemical Symbol: AlMg4,5Mn0,7
Temper: cast tempered Quantity tolerance: +/- 10% Shape of block: Blocks must be Sawn in both ends. Flat edged. Block's max weight: 11.000 kg Transportation & Loading of Truck: Loading from the side Loading only using forklift Packing lists: must contain charge number	Important norms and literature EN 573-3 EN 515 EN 487, EN 515, EN 573-3 Mechanical composition: - Hardness: min 70 HB - RM: min 240 / max 290 MPa - RP0.2: min 110 / max 130 MPa

Homogenized aluminum blocks in alloy EN AW-7021 cast temp

EN AW 7021 – Aluminium blocks Alumeco ApS	Alloy name: 7021 International alloy name: EN AW 7021 Chemical Symbol: Al Zn5,5Mg1,5
Temper: cast tempered Quantity tolerance: +/- 10% Shape of block: Blocks must be Sawn in both ends. Flat edged. Roughness Ra = <15 µm Block's max weight: 11.000 kg Transportation & Loading of Truck: Loading from the side Loading only using forklift Packing lists: must contain charge number	Important norms and literature EN 573-3 EN 515 EN 487, EN 515, EN 573-3

Aluminium cast milled plate in alloy - EN AW-5083 O3
--

EN AW 5083 – Aluminium cast milled plate Alumeco ApS	Alloy name: 5083 International alloy name: EN AC 5083 Chemical Symbol: AlMg4,5Mn0,7
Temper: 03 Quantity tolerance: +/- 10% Thickness Tolerance: +/-0,1mm Foil on both sides Flatness: for thickness 5mm - 0,8mm/m for thickness 6 – 12,7mm - 0,4mm/m for thickness >12,7mm - 0,13mm/m Roughness Ra 0,4 µm	Important norms and literature EN 573-3 EN 515 EN 487, EN 515, EN 573-3 Mechanical properties: Hardness: min 70 HB RM: min 240 / max 290 MPa RP0.2: min 110 / max 130 MPa

Aluminium cast milled plate in alloy - EN AW-5754 V-cast O3

EN AW 5083 – Aluminium cast milled plate Alumeco ApS	Alloy name: 5754 International alloy name: EN AW 5754 Chemical Symbol: IMg3
Temper: O3 Quantity tolerance: +/- 10% Thickness Tolerance: +0/-0,1mm Foil on both sides Flatness: for thickness <=10mm - 0,2 mm/m for thickness >10mm - 0,2 mm/m Roughness Ra 0,8 µm	Important norms and literature EN 573-3 EN 515 EN 487, EN 515, EN 573-3 Mechanical properties: Hardness: min 50 HB RM: min 180 RP0.2: min 72